

Boca's Turbo 650[™] gives you the flexibility to add on exciting peripherals at an unbelievable low cost!

Maximum Speed

The Turbo 650 blazes at 460.8 Kbps, four times faster than regular I/O cards. It is the perfect match for the latest high-speed modems, especially 56K and ISDN.

Multiple Connectivity

Connect multiple peripheral products such as modems, serial printers, mice and most other serial devices. Compatible with ISA systems, the Turbo 650 features a convenient design that allows it to be installed in either an 8- or 16-bit slot.

Newest Technology

The Turbo 650 features technology using the I6C650 chip. It increases performance and significantly reduces system overhead. 32-byte FIFO buffers send and receive data at maximum speed between the host PC and its serial devices. Also full modem controls signals ensure that external modems will recognize the serial port. Maximize Your PC's Performance with High-Speed Connections

Includes two serial ports

Four times the speed of a regular I/O card

- Perfect for the latest high-speed modems and ISDN terminal adapters
- Easy to install and set up

PTIMIZES YOU





ULTRA-HIGH-SPEED I/O INTERFACE

EASY INSTALLATION

The Turbo 650 is designed to install in any IBM-compatible PC. Just follow the easy-to-read, step-by-step instructions and you will have your connections up and running in minutes.

CONTENTS

Ultra-high-speed serial adapter
Driver diskette
Documentation

OTHER BOCA PRODUCTS

From cruising the Internet at breakthrough speeds to linking computer peripherals, Boca helps you make the high-speed connections you need to compete in a high-tech world. Boca's products combine excellence in design and engineering, ISO-certified manufacturing, full features and attractive prices to give you an outstanding value. Boca's current product categories include

Modems I/O (input/output) cards

SPECIFICATIONS

- Designed for use in a 16- or 8-bit slot
- Serial port speeds up to 460.8 Kbps
- Includes two DB-9 connectors
- Jumper-selectable I/O addresses and interrupts:
 - Serial A: COM1, 2, 3, 4
 - or disabled; IRQ 3, 4, 5 or 9 - Serial B: COM1, 2, 3, 4
 - or disabled; IRQ 3, 4, 5 or 9 – Clock set: selectable
 - addresses for baud rates exceeding 115 Kbps

ENVIRONMENTAL

- Relative humidity: 70% (non-condensing)
- Operating temperature: 20 to 50° C.

PKG. DIMENSIONS

■ L 8 ¹/4″ x W 1 ⁵/8″ x H 6 ¹/8″

Maximize Your PC's Performance with High-Speed Connections



VARRANT

UNION DESCRIPTION OF THE OWNER OF

JPTIMIZES YO

V.90

NODEN

- Product Information: Internet: http://www.bocaresearch.com QuickFax: (561) 995-9456
- Customer Support: Voice: (561) 241-8088 E-mail: support@bocaresearch.com Fax: (561) 997-2163

Boca Research, Inc. 1601 Clint Moore Road Boca Raton, Florida 33487-2747 USA

IO652 UPC: 7-28055-12122-7 MO80 • Revision 2.0 • 8/98



ULTRA-HIGH-SPEED I/O INTERFACE