Product Specifications



Product Code: M144EE Product Name: International 14.4Kbps Modem by Boca

- ◆Data transmission rates of 14.4K, 12K, 9600, 7200, 4800, 2400, 1200, or 300bps.
- 100% data compatibility with the Hayes 'AT' command set.
- Programmable speaker volume control.
- Automatic voice and data switching.
- ♦ Auto-speed sensing.
- V.32bis, V.42bis, and MNP5 are supported as well as V.42 and MNP2-4 error correction, offering throughput speed of 57,600bps.
- Group III send and receive fax capability with support for Class 1 and Class 2 fax commands.
- Supports 100 x 196 high resolution and 100 x 98 low resolution.
- ♦ 220 volt power adapter

Modem Data Rate: 14.4K, 12K, 9600, 7200, 4800, 2400, 1200, or 300bps

Fax Data Rate: 14.4K, 12K, 9600, 7200, 4800, 2400bps.

Protocol Compatibility:

V.32bis (14.4Kbps), V.32 (9600bps), V.42, V.22 (2400bps), V.21 (1200bps)

Bell: Bell 212A (1200bps), Bell 103 (300bps)

Fax Modulation Protocols

V.17 (14,400/12,000bps) transmit and receive V.29 (9600/7200bps) transmit and receive V.27ter (4800/2400bps) transmit and receive V.21 channel 2 (300bps) transmit and receive

V.42/MNP2-4 and V.42bis/MNP5 support

LED Status Indicators: TM, AA, HS, OH, SD, RD, TR, CD

Diagnostics:

- Local/remote digital and analog loopback.
- Automatic power-on self-test.

Dimensions:

EXTERNAL: 18.42 CM x 13.67 CM x 3.18 CM **INTERNAL**: 10.80 CM x 10.49 CM 1377 Clint Moore Road • Boca Raton, FL 33487-2722, USA Tel: (407) 997-6227 • Fax: (407) 997-0918 • QuickFax: (407) 995-9456 Visit our Web site: http://www.boca.org

International Nodem





14.4Kbps External BOCAMODEM



© Boca Research, Inc. All references to computer products use trademarks owned by their respective manufacturer. Boca Research, Inc. is not liable for any errors or omissions. The information presented here is subject to change without notice. PSM144IE.PM5

Release 2.0 10/95